

3125RU5W



Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe
→ Socket Outlets for Panel Mounting

General Information

Extended Product Type:	3125RU5W
Product ID:	2CMA126718R1000
EAN:	7392696267182
Catalog Description:	IND. P&S#3125RU5W
Long Description:	Socket-outlet, panel mounting, 5h, 125A, IP67, unified flange, straight Clock Position Of Grounding Contact 5 hour Color code Black

Ordering

EAN:	7392696267182
Minimum Order Quantity:	1 piece
Country of Origin:	Czech Republic (CZ)

Dimensions

Product Net Width:	115 mm
Product Net Height:	158 mm
Product Net Length:	122 mm
Product Net Depth:	158 mm
Product Net Weight:	1 kg

Container Information

Package Level 1 Width:	135 mm
Package Level 1 Length:	140 mm
Package Level 1 Height:	200 mm
Package Level 1 Gross Weight:	1 kg
Package Level 1 EAN:	7392696267182
Package Level 1 Units:	1 piece
Package Level 2 Units:	174 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC700005D0001
Declaration:	2CMC700005D0001
Environmental Information:	2CMC700001D0002
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1614199

Additional Information

Additional Information:	3P+E
Cable Cross-Section:	16 ... 70 mm ²
Color:	Black
Connection Type:	Screw clamp
Degree of Protection:	IP67 IP69
Enclosure Material:	Thermoplastic polyester (PBT)
Frequency (f):	50 Hz 60 Hz
Housing Material:	Thermoplastic (PBT)
Invoice Description:	IND. P&S#3125RU5W
Mounting Holes:	71x71
Mounting Type:	unified flange, straight
Number of Poles:	4
Product Main Type:	TRU
Product Name:	Panel mounted socket
Protection Type:	Watertight
Rated Current (I_n):	125 A
Rated Voltage (U_r):	600 ... 690 V
Recommended Screw Driver:	PH2
RoHS Date:	L23
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Socket Outlets for Panel Mounting
Suitable for Product Class:	Industrial Plugs and Sockets

Classifications

eClass:	27440504
E-nummer:	99090254
UNSPSC:	39120000

