

Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe
→ Surface Socket Outlets

General Information

Extended Product Type:	332RS11
Product ID:	2CMA193134R1000
EAN:	7392696931342
Catalog Description:	Industrial Socket Outlets for Surface Mounting, 3P+E, 32 A, 440 ... 460 V
Long Description:	Surface socket-outlet, earthing sleeve position 11h, rated current 32A, IP4 4 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

Ordering

EAN:	7392696931342
Minimum Order Quantity:	10 piece
Country of Origin:	Czech Republic (CZ)

Dimensions

Product Net Width:	85 mm
Product Net Height:	118 mm
Product Net Length:	163 mm
Product Net Depth:	163 mm
Product Net Weight:	0.28 kg

Container Information

Package Level 1 Width:	188 mm
Package Level 1 Length:	175 mm
Package Level 1 Height:	428 mm
Package Level 1 Gross Weight:	2.8 kg
Package Level 1 EAN:	7392696661348
Package Level 1 Units:	10 piece
Package Level 2 Units:	240 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC700005D0001
Declaration:	2CMC700005D0001
Environmental Information:	2CMC700001D0002
SEMKO Certificate:	1613211

Additional Information

Additional Information:	3P+E
Cable Cross-Section:	2.5 ... 10 mm ²
Cable Diameter:	22 mm
Color:	Red
Connection Type:	Screw clamp
Degree of Protection:	IP44
Frequency (f):	60 Hz
Housing Material:	Plastic (PA)
Invoice Description:	Ind. P&S#332RS11
Mounting Holes:	111x72
Number of Poles:	4
Product Main Type:	ERS
Product Name:	Wall mounted socket
Protection Type:	Splashproof
Rated Current (I _n):	32 A
Rated Voltage (U _r):	440 ... 460 V
Recommended Screw Driver:	PH2
Standards:	IEC 60309-1 IEC 60309-2

Classifications

eClass:	27440510
E-nummer:	removed
UNSPSC:	39120000



