

232RS4



Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe
→ Surface Socket Outlets

General Information

Extended Product Type:	232RS4
Product ID:	2CMA193121R1000
EAN:	7392696931212
Catalog Description:	Surface socket-outlet, 4h, 32A, IP44, 2P+E
Long Description:	Surface socket-outlet, earthing sleeve position 4h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Yellow

Ordering

EAN:	7392696931212
Minimum Order Quantity:	10 piece
Country of Origin:	Czech Republic (CZ)

Dimensions

Product Net Width:	85 mm
Product Net Height:	118 mm
Product Net Length:	163 mm
Product Net Depth:	163 mm
Product Net Weight:	0.3 kg

Container Information

Package Level 1 Width:	188 mm
Package Level 1 Length:	175 mm
Package Level 1 Height:	428 mm
Package Level 1 Gross Weight:	3 kg
Package Level 1 EAN:	7392696661218
Package Level 1 Units:	10 piece
Package Level 2 Units:	240 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC700005D0001
Declaration:	2CMC700005D0001
Environmental Information:	2CMC700001D0002
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1613211

Additional Information

Additional Information:	2P+E
Cable Cross-Section:	2.5 ... 10 mm ²
Cable Diameter:	22 mm
Cable Entry Position:	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
Color:	Yellow
Connection Type:	Screw clamp
Degree of Protection:	IP44
Enclosure Material:	Thermoplastic
Frequency (f):	50 Hz 60 Hz
Function:	Surface socket outlet
Housing Material:	Plastic (PA)
Invoice Description:	Ind. P&S#232RS4
Mounting Holes:	111x72
Number of Poles:	3
Product Main Type:	ERS
Product Name:	Wall mounted socket
Protection Type:	Splashproof
Rated Current (I_n):	32 A
Rated Voltage (U_r):	100 ... 130 V
Recommended Screw Driver:	PH2
RoHS Date:	L23
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Surface Socket Outlets
Suitable for Product Class:	Industrial Plugs and Sockets

Classifications

eClass:	27440510
E-number:	2416490
UNSPSC:	39120000

