

Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

General Information

Extended Product Type:	363C6
Product ID:	2CMA166850R1000
EAN:	7392696668507
Catalog Description:	Ind. P&S#363C6
Long Description:	Connector, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

Ordering

EAN:	7392696668507
Minimum Order Quantity:	1 piece
Country of Origin:	Czech Republic (CZ)

Dimensions

Product Net Width:	98 mm
Product Net Height:	112 mm
Product Net Length:	224 mm
Product Net Depth:	224 mm
Product Net Weight:	0.8 kg

Container Information

Package Level 1 Width:	114 mm
Package Level 1 Length:	114 mm
Package Level 1 Height:	230 mm
Package Level 1 Gross Weight:	0.88 kg
Package Level 1 EAN:	7392696668507
Package Level 1 Units:	1 piece
Package Level 2 Units:	171 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC700005D0001
Declaration:	2CMC700005D0001
Environmental Information:	2CMC700001D0002
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1614200

Additional Information

Additional Information:	3P+E
Cable Cross-Section:	4 ... 16 mm ²
Cable Entry Position:	Cable entry, membrane
Color:	Red
Connection Type:	Screw clamp
Degree of Protection:	IP44
Enclosure Material:	Thermoplastic polyester (PBT)
Frequency (f):	50 Hz 60 Hz
Function:	Connector
Housing Material:	Thermoplastic (PBT)
Invoice Description:	Ind. P&S#363C6
Number of Poles:	4
Product Main Type:	TC
Product Name:	Industrial Connector
Protection Type:	Splashproof
Rated Current (I_n):	63 A
Rated Voltage (U_r):	380 ... 415 V
Recommended Screw Driver:	PH2
RoHS Date:	L23
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Connectors
Suitable for Product Class:	Industrial Plugs and Sockets

Classifications

eClass:	27440509
E-nummer:	2416350
UNSPSC:	39120000

