

Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe  
→ Socket Outlets for Panel Mounting

## General Information

<b>Extended Product Type:</b>	432RU6
<b>Product ID:</b>	2CMA193259R1000
<b>EAN:</b>	7392696932592
<b>Catalog Description:</b>	Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E
<b>Long Description:</b>	Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

## Ordering

<b>EAN:</b>	7392696932592
<b>Minimum Order Quantity:</b>	10 piece
<b>Country of Origin:</b>	Czech Republic (CZ)

## Dimensions

<b>Product Net Width:</b>	75 mm
<b>Product Net Height:</b>	102 mm
<b>Product Net Length:</b>	105 mm
<b>Product Net Depth:</b>	105 mm
<b>Product Net Weight:</b>	0.24 kg

## Container Information

<b>Package Level 1 Width:</b>	154 mm
<b>Package Level 1 Length:</b>	182 mm
<b>Package Level 1 Height:</b>	378 mm
<b>Package Level 1 Gross Weight:</b>	2.4 kg
<b>Package Level 1 EAN:</b>	7392696662598
<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 2 Units:</b>	480 piece

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	2CMC700005D0001
<b>Declaration:</b>	2CMC700005D0001
<b>Environmental Information:</b>	2CMC700001D0002
<b>RoHS Information:</b>	2CMC700057D0001

**SEMKO Certificate:** 1613211

## Additional Information

<b>Additional Information:</b>	3P+N+E
<b>Cable Cross-Section:</b>	2.5 ... 10 mm <sup>2</sup>
<b>Color:</b>	Red
<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	IP44
<b>Enclosure Material:</b>	Thermoplastic
<b>Frequency (f):</b>	50 Hz 60 Hz
<b>Function:</b>	Socket outlet, panel mounting, unified flange, straight
<b>Housing Material:</b>	Plastic (PA)
<b>Invoice Description:</b>	Ind. P&S#432RU6
<b>Mounting Holes:</b>	61x61
<b>Mounting Type:</b>	unified flange, straight
<b>Number of Poles:</b>	5
<b>Product Main Type:</b>	ERU
<b>Product Name:</b>	Panel mounted socket
<b>Protection Type:</b>	Splashproof
<b>Rated Current (I<sub>n</sub>):</b>	32 A
<b>Rated Voltage (U<sub>r</sub>):</b>	200/346 ... 240/415 V
<b>Recommended Screw Driver:</b>	PH2
<b>RoHS Date:</b>	L23
<b>Standards:</b>	IEC 60309-1 IEC 60309-2
<b>Suitable For:</b>	Socket Outlets for Panel Mounting
<b>Suitable for Product Class:</b>	Industrial Plugs and Sockets

## Classifications

<b>eClass:</b>	27440504
<b>E-nummer:</b>	2416660
<b>UNSPSC:</b>	39120000

