


The ETHERNET PLC combines control functionality, I/O interface and ETHERNET in one device.

Programming of the application is done in accordance with IEC 61131-3. Function blocks allow both clients and servers to be programmed via socket APIs for all transport protocols (e.g., TCP, UDP).

Features and applications:

- Use of decentralized control can better support a PLC or PC
- Complex applications can be divided into individually testable units
- Programmable fault response in the event of a fieldbus failure
- Signal pre-processing reduces fieldbus transmissions
- Peripheral equipment can be controlled directly, resulting in faster system response times
- Stand-alone, compact controller

Description	Item No.	Pack. Unit	System Data
ETHERNET Controller 10 MBit	750-843	1	No. of controllers connected to Master limited by ETHERNET specification
			Transmission medium Twisted Pair S-UTP 100 Ω cat. 5
			Max. length of fieldbus segment 100 m between hub station and 750-843; max. length of network limited by ETHERNET specification
			Baud rate 10 Mbit/s
			Buscoupler connection RJ-45
			Protocols MODBUS/TCP, HTTP, BootP, MODBUS/UDP
Accessories	Item No.	Pack. Unit	Programming WAGO-I/O-PRO V2.3
WAGO-I/O-PRO V2.3, RS-232 kit	759-333	1	IEC 61131-3 IL, LD, FBD (CFC), ST, FC
Miniature WSB Quick marking system			
plain	248-501	5	
with marking	see Section 11		
Approvals			
Conformity marking	CE		
Korea Certification	KC		
Marine applications	ABS, BV, DNV, GL, KR, LR, NKK, PRS, RINA		
UL 508			
ANSI/ISA 12.12.01	Class I, Div. 2, Grp. ABCD, T4		
ATEX 554086 X	I M2 Ex d I Mb, II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T135°C Dc		
IECEx TUN 09.0001 X	Ex d I Mb, Ex nA IIC T4 Gc, Ex tc IIIC T135°C Dc		



Technical Data

Number of I/O modules	64
Max. input process image	512 bytes
Max. output process image	512 bytes
Max. input variables	512 bytes
Max. output variables	512 bytes
Configuration	automatic
Program memory	64 Kbytes
Data memory	64 Kbytes
Non-volatile memory (retain)	8 Kbytes
Cycle time	< 3ms for 1,000 statements / 256 dig. I/Os
Power supply	24 V DC (-25 % ... +30 %)
Max. input current (24 V)	500 mA
Power supply efficiency	87 %
Internal current consumption (5 V)	200 mA
Total current for I/O modules (5 V)	1800 mA
Isolation	500V system/supply
Voltage via power jumper contacts	24 V DC (-25 % ... +30 %)
Current via power jumper contacts (max.)	10 A DC

General Specifications

Operating temperature	0 °C ... +55 °C
Wire connection	CAGE CLAMP®
Cross sections	0.08 mm² ... 2.5 mm² / AWG 28 ... 14
Strip lengths	8 ... 9 mm / 0.33 in
Dimensions (mm) W x H x L	51 x 65 x 100
	Height from upper-edge of DIN 35 rail
Weight	197 g
Storage temperature	-25 °C ... +85 °C
Relative air humidity (no condensation)	95 %
Vibration resistance	acc. to IEC 60068-2-6
Shock resistance	acc. to IEC 60068-2-27
Degree of protection	IP20
EMC immunity of interference	acc. to EN 61000-6-2, marine applications
EMC emission of interference	acc. to EN 61000-6-4, marine applications