


PRODUCT-DETAILS

316R9

Socket-outlet, panel mounting, 9h, 16A, IP44, minimized flange, straight, 3P+E



Informações gerais

Extended Product Type	316R9
Product ID	2CMA193156R1000
EAN	7392696931564
Catalog Description	Socket-outlet, panel mounting, 9h, 16A, IP44, minimized flange, straight, 3P+E
Long Description	Panel mounted socket, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue

Ordering

E-Number (Sweden)	E2416611
E-Number (Finland)	2421200
E-Number (Norway)	2416611
EAN	7392696931564
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	66 mm
Product Net Height	87 mm
Product Net Weight	0.25 kg

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	7392696661560
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1670 kg
Package Level 2 EAN	7392696079853
Package Level 2 Units	pallet (lift) 660 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316R9
Mounting Holes	51x51
Mounting Type	Minimized straight flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ER
Product Name	Panel mounted socket

Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categorias

Produtos e Sistemas de Baixa Tensão → Plugues e soquetes industriais → Easy & Safe → Tomada para Montagem em Painel

