

PRODUCT-DETAILS

CA4-22M

CA4-22M Auxiliary Contact Block



Informações gerais	
Tipo de produto alargado	CA4-22M
ID do produto	1SBN010140R1122
EAN	3471523130166
Descrição do catálogo	CA4-22M Auxiliary Contact Block
Descrição longa	The auxiliary contact blocks are used for the operation of auxiliary circuits and control circuits for standard industrial environments. Types of auxiliary contact blocks for front mounting: • CA4 1 or 4-pole block, with instantaneous N.O., N.C. contacts • CC4 1-pole block, with N.O. leading contact or N.C. lagging contact • CAT4 2-pole block, with instantaneous N.O. + N.C. contacts and A1 / A2 coil terminal connection on front face. Select the 4-pole auxiliary contact blocks CA4-..E, CA4-..M, CA4-..U or CA4-..N type, according to the contactor or contactor relay type for compliance with the standard requirements (see "Terminal marking and positioning"). Types of auxiliary contact blocks for side mounting: • CAL4 2-pole block, with instantaneous N.O. + N.C. contacts. For clipping onto the right- and/or left-hand side of the contactors. The auxiliary contact blocks are equipped with screw type connecting terminals delivered open, protected against accidental direct contact and bear the corresponding function marking.

Technical	
Adequado para	AF09 AF09Z AF12 AF12Z AF16 AF16Z AFC09 AFC12 AFC16

AF09B
AF09ZB
AF12B
AF12ZB
AF16B
AF16ZB

Tensão operacional nominal	Auxiliary Circuit 690 V
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Frequência nominal (f)	Auxiliary Circuit 50 / 60 Hz
Number of Auxiliary Contacts NC	2
Number of Auxiliary Contacts NO	2
Low Coil Consumption	No
Binário de aperto	Auxiliary Circuit 1.2 N·m
Mounted Auxiliary Contacts	2 NO, 2 NC
Tipo de apoio	Front mounting
Wire Stripping Length	Auxiliary Circuit 10 mm
Tipo de terminal	Screw Terminals

Environmental

Grau de proteção	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Estado RoHS	Following EU Directive 2011/65/EU
Informação ambiental	1SBD250143E1000

Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 11 in·lb
Pilot Duty UL/CSA	A600 Q600

Dimensions

Largura Líquida do Produto	43 mm
Altura Líquida do Produto	43 mm
Profundidade/Comprimento Líquidos do Produto	39.5 mm
Peso Líquido do Produto	0.055 kg

Container Information

Unidades de embalagem Nivel 1	box 1 piece
Largura da embalagem	46 mm

Nível 1

Altura da embalagem Nível 1	46 mm
Profundidade/Comprimento da embalagem Nível 1	46 mm
Peso bruto da embalagem Nível 1	0.055 kg
Nível de Embalagem 1 EAN	3471523130166
Unidades de embalagem Nível 2	box 192 piece
Peso bruto da embalagem Nível 2	10.56 kg
Package Level 3 Units	4608 piece

Ordering

Quantidade Mínima de Encomenda	1 piece
Número de tarifa aduaneira	85389099
E-Number (Finland)	3706515
E-Number (Sweden)	3211420

Certificates and Declarations (Document Number)

Certificado ABS	ABS_20-2060694-PDA
Certificado BV	BV_2634H24900B0
CB Certificate	CB_SE-93053
CQC Certificate	CQC2011010304496319 CQC2013010304651497
Certificado cUL	UL_20180227_E252354_3_1
Declaration of Conformity - CCC	2020980304001258 2020980304001259
Declaração de conformidade -CE	1SBD250007U1000
Declaration of Conformity - UKCA	1SBD250038U1000
Certificado DNV	DNV-GL_TAE00001BV-3
DNV GL Certificate	DNV-GL_TAE00001BV-3
EAC Certificate	EAC_RU C-FR ME77 B03391
Informação ambiental	1SBD250143E1000
Certificado GL	DNV-GL_TAE00001BV-3
Certificado GOST	GOST_POCCFR.ME77.B07175.pdf
Instruções e Manuais	1SBC101041M6801
Certificado LR	LRS_1300087E1
Certificado RINA	RINA_ELE084013XG
Certificado RMRS	RMRS_1802703280
Informação RoHS	1SBD250007U1000
Certificado UL	UL_20091128-E252354-3-1
UL Listing Card	UL_E252354

Popular Downloads

Instruções e Manuais	1SBC101041M6801
UL Listing Card	UL_E252354

Classifications		
ETIM 7	EC000041 - Auxiliary contact block	
ETIM 8	EC000041 - Auxiliary contact block	
Categoria REEE	5. Small Equipment (No External Dimension More Than 50 cm)	
REEE B2C / B2B	Business To Business	
CN8	8538 90 99	
UNSPSC	39121500	
eClass	V11.0 : 27371302	
Código de classificação do objeto	K	

Categorias

Produtos e Sistemas de Baixa Tensão → Produtos para controle → Contatores → Acessórios para Contatores

