

PRODUCT-DETAILS

OVR T2-T3 20-275 P QS

OVR T2-T3 20-275 P QS Surge Protective Device



General Information

Extended Product Type	OVR T2-T3 20-275 P QS
Product ID	2CTB803871R2400
EAN	3660308519566
Catalog Description	OVR T2-T3 20-275 P QS Surge Protective Device
Long Description	OVR T2-T3 20-275 P QS Surge Protective Device

Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-C TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U_r)	400 V AC
Nominal AC Voltage of the System (U_o)	230 / 400 V
Voltage Rating DC	350 V
Voltage Protection Level (U_p)	1 kV (L-N) - kV (N-PE) - kV (L-PE) 0.9 kV
Maximum Continuous Operating Voltage (U_c)	(L-PE) 275 V (L-L) 275 V (L-N) 275 V (N-PE) - V

Temporary Overvoltage Test Value (U_T)	337 V
Rated Service Short-Circuit Breaking Capacity (I_{cs})	100 kA
Discharge Current	Nominal 5 kA Maximum 20 kA Total 20 kA Nominal (8 / 20 μ s) 5 kA I (max, 8 / 20 μ s) 20 kA
Impulse Current	I (imp, 10 / 350 μ s) 2 kA
Short Circuit Withstand I_{cc}	100 kA
Power Loss	8 mW
Short-Circuit Protective Devices	Curve B Breakers $\leq$ 125 A Curve C Breakers $\leq$ 125 A gL Type Fuses $\leq$ 125 A gG Type Fuses $\leq$ 125 A
Arrester Class	II III
Number of Poles	1
Number of Protected Poles	1
Number of Conductors	1
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN rail (top hat rail) 35 mm
Product Type	QS
Options Provided	Residential or other where accurate protection is needed.
Auxiliary Circuit Load	Minimum - Maximum -
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	1 modular spacing

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	17.8 mm
Product Net Height	88 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.12 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	117 mm
Package Level 1 Height	82 mm
Package Level 1 Depth / Length	25 mm

Package Level 1 Gross Weight	145 g
Package Level 1 EAN	3660308519566

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Bulgaria (BG)

Certificates and Declarations (Document Number)

CB Certificate	2CTC432024G1701
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410
Instructions and Manuals	2CTC432097M1701

Popular Downloads

Data Sheet, Technical Information	2CTC432206D0201
Instructions and Manuals	2CTC432097M1701
Mechanical Drawings	2CTC800021F0100.pdf 2CTC800021F0101.dxf 2CTC800021F0102.stp 2CTC800021F0103.igs

Classifications

ETIM 7	EC000941 - Surge protection device for power supply systems
ETIM 8	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141ECC

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II → Type T2 - T3 20kA

