

S5N**DATALOGIC**

EXTENDED RANGE OF STANDARD “ONE FOR ALL” PHOTOELECTRIC TUBULAR M18 SENSORS

- All optic functions
- Improved EMI immunity
- Improved ambient light immunity
- Improved laser safety level
- M18 flat plastic with universal mounting
- Short plastic housing models
- Available in M18 metal housing
- Stainless steel housing models
- Axial or radial optics, cable or connector
- Standard 4-wire NO-NC NPN or PNP output
- M12 pigtail models available
- IO-Link connectivity V1.1 with double channel



(*) Stainless steel models. ATEX II 3DG

APPLICATIONS

- Processing and Packaging machinery
- Conveyor lines, material handling
- Ceramics intralogistics
- Automated warehousing

S5N		
Through beam		0...25 m (S5N-PP/NN; S5N-Px/Mx...PK/NK models) 0...20 m (S5N-SA/NA models) 0...60 m (class 1 LASER S5N...PP/NN models)
Retroreflective (on R2 reflector)		0,1...4 m (S5N-PP/NN; S5N-Px/Mx...PK/NK models)
Polarized retroreflective (on R2 reflector)		0,1...3m (S5N-Px/Mx...PK/NK models) 0,1...4 m (S5N...PP/NN; S5N-SA/NA models) 0,1...16 m (class 1 LASER S5N...PP/NN models)
Retroreflective for transparent (on R2 reflector)		0,1...0,8 m (S5N-SA/NA) 0,1...1,3 m (S5N...PP/NN models)
Diffuse proximity		short distance 0...100 mm (all models) medium distance 0...400 mm (S5N...PP/NN models) medium distance 0...350 (S5N-SA/NA models) medium distance 0...450 (S5N-Px/Mx...PK/NK models) long distance 0...700 ammm (S5N...PP/NN models) long distance Laser 0...350 mm (S5N...PP/NN models)
Fixed focus		50 mm (S5N-SA/NA models) 100 mm (S5N...PP/NN models)
Background suppression		40...120 mm (S5N-SA/NA models) 50...150 mm (S5N...PP/NN models)
Through beam with fiber optic		0...100 mm (S5N...PP/NN models)
Diffuse proximity with fiber optic		0...30 mm (S5N...PP/NN models)
Contrast sensor		10 ±2 mm (S5N...PP/NN models)
Luminescence sensor		0...20 mm (S5N...PP/NN models)
Power supply	VDC	10...30 V
	VAC	
	VAC/DC	
Output	PNP	•
	NPN	•
	NPN/PNP	
	relay	
	other	IO-Link v 1.1
Connection	cable	•
	connector	•
	pig-tail	•
Approximate dimensions (mm)		M18 x (see mechanical drawings)
Housing material		PBT, Nickel plated Brass (S5N-PP/NN; S5N-Px/Mx...PK/NK models) ABS, AISI 316 L Stainless steel inox (S5N-SA/NA models)
Mechanical protection		IP67 (S5N-PP/NN; S5N-Px/Mx...PK/NK models) IP65 - IP67 - IP69K (S5N-SA/NA)

TECHNICAL DATA

Power supply	10 to 30 VDC (limit values all models)
Ripple	2 VPP max. (all models)
Consumption (output current excluded)	35 mA max. (all models)
Light emission	red LED 630 nm (mod. S5N...D00/E01, S5N-PA/MA...M03) red LED 660 nm (mod. S5N...B01...PP/NN/PK/NK; S5N...T01...PP/NN) - (mod. S5N-SA/NA...B/D/T/M) red LED 670 nm (mod. S5N-PS/MS...M03...PP/NN) IR LED 880 nm - (mod. S5N-Px/Mx...A00/C01/C10/C21/G00...PP/NN/PK/NK) - (mod. S5N-SA/NA...A/C/G) white LED 400-700 nm (mod. S5N...W03...PP/NN) UV LED 370 nm (mod. S5N...U03...PP/NN) red Laser 650 nm (mod. S5N-PH/PL...G00/B01/C01...PP/NN)
Setting	Sensivity trimmer 270° and without trimmer model (see mech drawings) 4 turns sensitivity trimmer (mod. S5N-Px/Mx...M01...PK/NK) teach-in push-button (mod. S5N...M03/W03/U03...PP/NN)
Operating mode	LIGHT mode on N.O. output / DARK mode on N.C. output (mod.S5N...C01/C10/C21/D00/M03/U03...PP/NN) DARK mode on N.O. output / LIGHT mode on N.C. output (mod.S5N...A00/B01/E01/F01/T01/W03...PP/NN) L/D input white wire or pin 2, if pin not connected on S5N-Px/Mx...PK/NK: LIGHT mode (mod. S5N-Px/Mx...C/D/M...PK/NK) DARK mode (mod. S5N-Px/Mx...A/B/T/F...PK/NK) white wire or pin 2 connected to: 0 V DARK mode, +VCC LIGHT mode
Indicators	yellow OUTPUT LED (S5N, excl. mod. G00) green STABILITY LED (mod. S5N...B01/C01/C21/E01/F01/W03/U03), POWER LED (mod. S5N...G00) green/red READY/ERROR LED (mod. S5N...M03...PP/NN)
Output	PNP or NPN; NO; NC (mod. S5N...PP/NN) PNP or NPN (mod. S5N-Px/Mx...PK/NK) IO-Link v 1.1 (mod.S5N...OZ)
IO-Link interface	(mod.S5N...OZ) v 1.1, com 2, 38, 4 kBaud, 32 bit process data, 5 ms cycle time LED emission model, 8 ms cycle time LASER emission model
Output current	100 mA max. (all models)
Saturation voltage	2 V max. (all models)
Response time	0.5 ms (mod. S5N...A00/B01/T01/C10/C21/C01/D00/E01/U03...PP/NN) - (mod. S5N-Px/Mx...D00...PK/NK) 2 ms (mod. S5N...F01/G00...PP/NN) - (mod. S5N-Px/Mx...F00...PK/NK) 1 ms (mod. S5N...M03...PP/NN) - (mod. S5N-Px/Mx...A/B/C/T/M...PK/NK) 100 µs (mod. S5N...W03...PP/NN) 333 µs (mod. S5N-PH/PL...PP/NN Laser emission models)
Switching frequency	1 kHz (mod. S5N...A00/B01/T01/C10/C21/C01/D00/E01/U03...PP/NN) - (mod. S5N-Px/Mx...D00...PK/NK) 250 Hz (mod. S5N...F01/G00...PP/NN) - (mod. S5N-Px/Mx...F00...PK/NK) 500 Hz (mod. S5N...M03...PP/NN) - (mod. S5N-Px/Mx...A/B/C/T/M...PK/NK) 100 µs (mod. S5N...W03...PP/NN) 333 µs (mod. S5N...PP/NN Laser emission models)
Connection	M12 4-pole connector, 2 m cable Ø 4 mm, 150 mm length Ø 4 mm cable with M12 4-pole connector
Dielectric strength	500 VAC, 1 min between electronics and housing
Insulating resistance	>20 MΩ, 500 VDC between electronics and housing
Electrical protection	Class 2
Mechanical protection	IP67 (S5N-PP/NN; S5N-Px/Mx...PK/NK models) IP65 - IP67 - IP69K (S5N-SA/NA)
Ambient light rejection	According to EN 60947-5-2
Vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
Shock resistance	11 ms (30 G) 6 shock for every axis (EN60068-2-27)
Housing material	PBT, Nickel plated Brass (S5N-Px/Mx...PP/NN/PK/NK models) ABS, AISI 316 L Stainless steel inox (S5N-SA/NA models)
Lens material	PMMA (all models)
Operating temperature	-25 to 55 °C (Laser mod.) -10 to 50 °C
Storage temperature	-25 to 70 °C
Weight	Plastic version 75 g max. cable vers. (90 g max. mod. M03), 25 g max. conn. vers. (40 g max. mod. M03) Metal version 110 g max. cable vers. (125 g max. mod. M03), 60 g max. conn. vers. (75 g max. mod. M03)

PLASTIC

Technical drawing of the LED module showing top and side views with dimensions.

Top View Dimensions:

- Overall length: L
- Distance from left edge to first LED: 1.4
- Distance between first and second LED: 2
- Distance between second and third LED: 1.5
- Distance from third LED to right edge: 14.5
- Distance from left edge to first LED (alternative): 3.5
- Distance between first and second LED (alternative): 4
- Distance between second and third LED (alternative): 4

Side View Dimensions:

- Overall height: 25
- Distance from left edge to first LED: 2.5
- Distance from first LED to TRIMMER: X
- Distance from TRIMMER to OUTPUT LED: 10
- Distance from left edge to first LED (alternative): 1
- Distance from first LED to second LED: 15
- Distance from second LED to TRIMMER: $X1$
- Distance from TRIMMER to OUTPUT LED (alternative): 10

Other Labels:

- M8x1
- N° 2 $\varnothing 3.8$
- TRIMMER
- STABILITY LED
- OUTPUT LED
- M7

	MODELS	
	with trimmer	without trimmer
L	67	57
X	43	42
X1	34	24

	MODELS	
	with trimmer	without trimmer
L	79	69
X	43	42
X1	46	36

The technical drawing consists of two views of the LED module:

- Top View:** Shows the overall length L and the distance between the two LEDs, which is 4 units. The total width of the module is 14.5 units.
- Side View:** Shows the height of the module, which is 2.5 units. The distance from the left edge to the center of the LEDs is X units. The distance from the center of the LEDs to the right edge is 10 units. The right edge has a width of $5 \text{ M} \pm 2$ units. The module is labeled with "TRIMMER" and "OUTPUT LED". A "STABILITY LED" is also indicated.


	MODELS	
	with trimmer	without trimmer
L	67	57
X	43	38

	MODELS	
	with trimmer	without trimmer
L	79	69
X	43	38


[illegible]

BACKGROUND SUPPRESSION AXIAL VERSION

PLASTIC




METAL




BACKGROUND SUPPRESSION RADIAL VERSION

PLASTIC




METAL




LUMINESCENCE AND CONTRAST

PLASTIC




METAL




DIMENSIONS

S5N-Px/Mx...PK/NK MODELS


AXIAL VERSION




RADIAL VERSION




CABLE VERS




CABLE VERS.




CH.24 PLASTIC NUTS




CH.22 PLASTIC NUTS




AXIAL VERSION



RADIAL VERSION




CABLE VERSION




S5N-SA MODELS

PLASTIC


M12 connector version




Cable version




Through beam emitter - M12 connector version




Background suppression - M12 connector version



Through beam emitter - cable version



Diffuse proximity - cable version



STAINLESS STEEL

Technical drawing of the LED module showing front, side, and perspective views with dimensions:

- Front View (Top Left):** Shows a hexagonal base with a central lens. Dimensions include a total width of 24 mm, a lens diameter of 16.6 mm, and a mounting hole diameter of 18.4 mm. The lens is labeled "OUTPUT LED" and the base is labeled "STABILITY LED". A mounting hole is labeled "M 12".
- Side View (Top Right):** Shows the module's profile with a total length of 48.7 mm. The mounting hole is labeled "M 12".
- Side View (Bottom Right):** Shows the module's profile with a total length of 32.85 mm. The mounting hole is labeled "M 12". A "TRIMMER" is indicated on the side.
- Perspective View (Bottom Left):** Shows the module from an angled perspective.
- Perspective View (Bottom Right):** Shows the module from an angled perspective.

[illegible]

Technical drawing of the LED module showing top, side, and isometric views with dimensions:

- Top View:**
 - Overall width: $\varnothing 24$
 - Distance from center to output LED: 17.1 mm
 - Distance from center to power LED: 17.1 mm
 - Distance between LEDs: 33.2 mm
 - Distance from center to mounting hole: 18.4 mm
 - Mounting hole diameter: $\varnothing 4.7$
 - Distance from center to mounting hole: 18.4 mm
 - Distance from center to mounting hole: 18.4 mm
- Side View:**
 - Overall length: 37.55 mm
 - Distance from mounting hole to output LED: 16.5 mm
 - Distance from mounting hole to power LED: 16.5 mm
 - Distance from mounting hole to output LED: 16.5 mm
 - Distance from mounting hole to power LED: 16.5 mm
 - Distance from mounting hole to output LED: 16.5 mm
 - Distance from mounting hole to power LED: 16.5 mm
- Isometric View:**
 - Shows the module with a 3D perspective.

Technical drawing of the cable gland assembly showing dimensions: Ø4, 150, Ø14.2, 47 max., and M12.

S5N...PP/NN MODELS

Through beam emitter

BROWN 1 + 10 ... 30 Vdc

WHITE 2 N.C. OUTPUT

BLACK 4 N.O. OUTPUT

BLUE 3 - 0 V

BROWN	1	+	10 ... 30 Vdc
WHITE	2		TEST +
BLACK	4		TEST / NOT USED (Laser version)
BLUE	3	-	0 V

N.C. OUTPUT (WHITE) + 10 ... 30 Vdc (BROWN)
 0 V (BLUE) - N.O. OUTPUT (BLACK)

N.C. OUTPUT
(WHITE) + 10 ... 30 Vdc
(BROWN)
0 V -
(BLUE) N.O. OUTPUT/IO-LINK
(BLACK)

G00 MODEL

BROWN 1 + 10 ... 30 Vdc
WHITE 2 TEST +
BLACK 4 TEST -
BLUE 3 - 0 V



A00/B01/C01/C10/C20/F00 MODELS

BROWN 1 + 10 ... 30 Vdc
 WHITE 2 LIGHT/DARK
 BLACK 4 NO OUTPUT
 BLUE 3 - 0 V




S5N...NA/SA MODELS

Cable and Pig-tail

BROWN	1	+12...30 VDC	BROWN	1	+12...30 VDC
WHITE	2	DARK/LIGHT*	WHITE	2	TEST+
BLACK	4	OUTPUT	BLACK	4	TEST-
BLUE	3	0 V	BLUE	3	0 V

Through beam emitter

M12 connector




Through beam emitter

INDICATORS AND SETTINGS

S5N...PP/NN MODELS


S5N-XX...A00/B01/C01/C21/E01/F01/T01



- A** OUTPUT status LED Yellow
STABILITY LED Green (Only Receiver)
POWER ON LED Green (Only Emitter)
- B** Adjustment trimmer (receiver)


Single-turn trimmer for sensitivity adjustment. Rotate in a clockwise direction to increase the operating distance.

S5N-XX-U03



- A** OUTPUT status LED Yellow
READY LED Green
LED Red error
- B** Teach-in push-button

S5N-XX-M03/W03




- A** OUTPUT status LED Yellow
READY LED Green
- B** Teach-in push-button

Teach-in button for setting.


EASYtouch™ provides two setting modes: standard or fine, both obtained by pressing the push-button only once. Please refer to instructions manual for operating details.

S5N-XX-A00/C10/D00



- A** A00/C10
OUTPUT status LED Yellow
- A** G00
OUTPUT status LED yellow
(Only Emitter G00)

S5N-Px/Mx...PK/NK MODELS




- A** OUTPUT status LED;
POWER ON LED on G00
model
- B** Adjustment trimmer
(B01, C01 models)
- C** M12 connector
- D** Cable connection


Trimmer for sensitivity adjustment.
Rotate in a clockwise direction to increase the operating distance.

S5N...SA/NA MODELS



Plastic/metal case with trimmer, M12 connector




A01, B01, C11, C31, T01, F01, M01




G01



Plastic, no trimmer, Cable, Pig Tail



A00, B00, C10, C00, T01, D50




G00

F00



DETECTION DIAGRAMS

S5N...PP/NN MODELS


THROUGH BEAM (G/F) INFRARED EMISSION







■ Recommended operating distance
■ Maximum operating distance



THROUGH BEAM (G/F) LASER RED EMISSION





■ Operating distance




RETROREFLECTIVE (A) INFRARED EMISSION



■ Operating distance







RETROREFLECTIVE POLARIZED (B) RED EMISSION




■ Recommended operating distance
■ Maximum operating distance

High efficiency reflectors can be used to obtain larger operating distances.
Refer to **Reflectors** (A.01).







RETROREFLECTIVE POLARIZED (B) LASER RED EMISSION




■ Operating distance

High efficiency reflectors can be used to obtain larger operating distances.
Refer to **Reflectors** (A.01).





RETROREFLECTIVE TRANSPARENT (T) RED EMISSION








■ Recommended operating distance
■ Maximum operating distance




High efficiency reflectors can be used to obtain larger operating distances. Refer to **Reflectors**.








ENERGETIC DIFFUSED (C) SHORT INFRARED EMISSION








ENERGETIC DIFFUSED (C) MID INFRARED EMISSION








ENERGETIC DIFFUSED (C) LONG INFRARED EMISSION






FIXED FOCUS (D) RED EMISSION






DIFFUSED (C) LASER RED EMISSION




BACKGROUND SUPPRESSOR (M) AXIAL RED EMISSION



BACKGROUND SUPPRESSOR (M) RADIAL RED EMISSION







FIBER OPTIC (E) RED EMISSION



Operating distance with standard fibers


Standard Fiber-optics:
OF-42-ST-20 proximity
OF-43-ST-20 through beam

High efficiency fiber-optics or accessory lenses
can be used to obtain larger operating distances.




* standard Fiber-optics

MARK READER (W) WHITE EMISSION




Operating distance




Operating distance

LUMINESCENCE (U) UV EMISSION




Operating distance



S5N...PK/NK MODELS


A00	3,5	4
Axial on R2		
A00	4	4,5
Axial on R5		
A00	2,5	3
Radial on R2		
A00	3	3,5
Radial on R5		








0 2,5 5 (m)



C10/C20	10
Axial	
C10	8
Radial	

0 5 10 (cm)












Note: the diagrams indicate the detection area typical of the axial optic versions; the maximum operating distance of the radial optic versions decreases as indicated in the tables given below

Recommended operating distance
Maximum operating distance

S5N-SA/NA MODELS



MODEL SELECTION AND ORDER INFORMATION

S5N - STANDARD PLASTIC HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-PA...PP/NN/OZ)					
OPTIC FUNCTION	EMISSION	CONNECTION	OUTPUT	MODEL	ORDER NO.
Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-A00-NN	952002091
		M12 Connector	PNP	S5N-PA-2-A00-PP	952002081
			NPN	S5N-PA-5-A00-NN	952002111
			PNP	S5N-PA-5-A00-PP	952002101
Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-B01-NN	952001611
		M12 Connector	PNP	S5N-PA-2-B01-PP	952001011
			NPN	S5N-PA-5-B01-NN	952001501
			PNP	S5N-PA-5-B01-PP	952001021
	LED, Radial optic	2m Cable	IO-Link	S5N-PA-5-B01-OZ	952002200
		M12 Connector	NPN	S5N-PR-2-B01-NN	952001781
			PNP	S5N-PR-2-B01-PP	952001031
			NPN	S5N-PR-5-B01-NN	952001721
			PNP	S5N-PR-5-B01-PP	952001041
	LASER, Axial optic	2m Cable	NPN	S5N-PL-2-B01-NN	952001871
		M12 Connector	PNP	S5N-PL-2-B01-PP	952001361
			NPN	S5N-PL-5-B01-NN	952001841
			PNP	S5N-PL-5-B01-PP	952001371
	LASER, Radial optic	2m Cable	IO-Link	S5N-PL-5-B01-OZ	952002250
		M12 Connector	NPN	S5N-PH-2-B01-NN	952001951
			PNP	S5N-PH-2-B01-PP	952001941
			NPN	S5N-PH-5-B01-NN	952001971
			PNP	S5N-PH-5-B01-PP	952001961
Long Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C01-NN	952001621
		M12 Connector	PNP	S5N-PA-2-C01-PP	952001051
			NPN	S5N-PA-5-C01-NN	952001511
			PNP	S5N-PA-5-C01-PP	952001061
	LED, Radial optic	2m Cable	IO-Link	S5N-PA-5-C01-OZ	952002210
		M12 Connector	NPN	S5N-PR-2-C01-NN	952001791
			PNP	S5N-PR-2-C01-PP	952001071
			NPN	S5N-PR-5-C01-NN	952001731
			PNP	S5N-PR-5-C01-PP	952001081
	LASER, Axial optic	2m Cable	NPN	S5N-PL-2-C01-NN	952001881
		M12 Connector	PNP	S5N-PL-2-C01-PP	952001381
			NPN	S5N-PL-5-C01-NN	952001851
			PNP	S5N-PL-5-C01-PP	952001391
	LASER, Radial optic	2m Cable	IO-Link	S5N-PL-5-C01-OZ	952002260
		M12 Connector	NPN	S5N-PH-2-C01-NN	952001991
			PNP	S5N-PH-2-C01-PP	952001981
			NPN	S5N-PH-5-C01-NN	952002011
			PNP	S5N-PH-5-C01-PP	952002001
Short Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C10-NN	952001631
		M12 Connector	PNP	S5N-PA-2-C10-PP	952001241
			NPN	S5N-PA-5-C10-NN	952001521
			PNP	S5N-PA-5-C10-PP	952001251
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-C10-NN	952001801
		M12 Connector	PNP	S5N-PR-2-C10-PP	952001491
			NPN	S5N-PR-5-C10-NN	952001741
			PNP	S5N-PR-5-C10-PP	952001481
Medium Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C21-NN	952002171
		M12 Connector	PNP	S5N-PA-2-C21-PP	952002161
			NPN	S5N-PA-5-C21-NN	952002191
			PNP	S5N-PA-5-C21-PP	952002181
Fixed focus	LED, Axial optic	2m Cable	NPN	S5N-PA-2-D00-NN	952001641
		M12 Connector	PNP	S5N-PA-2-D00-PP	952001091
			NPN	S5N-PA-5-D00-NN	952001531
			PNP	S5N-PA-5-D00-PP	952001101
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-D00-NN	952001811
		M12 Connector	PNP	S5N-PR-2-D00-PP	952001111
			NPN	S5N-PR-5-D00-NN	952001751
			PNP	S5N-PR-5-D00-PP	952001121
Fiber optic	LED, Axial optic	2m Cable	NPN	S5N-PA-2-E01-NN	952001651
		M12 Connector	PNP	S5N-PA-2-E01-PP	952001131
			NPN	S5N-PA-5-E01-NN	952001541
			PNP	S5N-PA-5-E01-PP	952001141
Through beam receiver	LED, Axial optic	2m Cable	NPN	S5N-PA-2-F01-NN	952001661
		M12 Connector	PNP	S5N-PA-2-F01-PP	952001151
			NPN	S5N-PA-5-F01-NN	952001551
			PNP	S5N-PA-5-F01-PP	952001161
Through beam receiver	LED, Radial optic	2m Cable	NPN	S5N-PR-2-F01-NN	952001821
		M12 Connector	PNP	S5N-PR-2-F01-PP	952001171
			NPN	S5N-PR-5-F01-NN	952001761
			PNP	S5N-PR-5-F01-PP	952001181
	LASER, Axial optic	2m Cable	NPN	S5N-PL-2-F01-NN	952001891
		M12 Connector	PNP	S5N-PL-2-F01-PP	952001401
			NPN	S5N-PL-5-F01-NN	952001861
			PNP	S5N-PL-5-F01-PP	952001411
	LASER, Radial optic	2m Cable	NPN	S5N-PH-2-F01-NN	952002031
		M12 Connector	PNP	S5N-PH-2-F01-PP	952002021
			NPN	S5N-PH-5-F01-NN	952002051
			PNP	S5N-PH-5-F01-PP	952002041
Through beam emitter	LED, Axial optic	2m Cable	-	S5N-PA-2-G00-XG	952001191
		M12 Connector	-	S5N-PA-5-G00-XG	952001201
			-	S5N-PR-2-G00-XG	952001211
			-	S5N-PR-5-G00-XG	952001221
	LASER, Axial optic	2m Cable	-	S5N-PL-2-G00-XG	952001421
		M12 Connector	-	S5N-PL-5-G00-XG	952001431
			-	S5N-PH-2-G00-XG	952002061
			-	S5N-PH-5-G00-XG	952002071

S5N - STANDARD PLASTIC HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-PA...PP/NN/OZ)

Background suppression	LED, Axial optic	2m Cable	NPN	S5N-PA-2-M03-NN	952001671	
			PNP	S5N-PA-2-M03-PP	952001231	
		M12 Connector	NPN	S5N-PA-5-M03-NN	952001561	
			PNP	S5N-PA-5-M03-PP	952001001	
	LED, Radial optic	M12 Connector	 IO-Link	S5N-PA-5-M03-OZ	952002230	
			PNP	S5N-PS-5-M03-PP	952001931	
			NPN	S5N-PS-5-M03-NN	952001921	
			PNP	S5N-PS-2-M03-PP	952001911	
Retroreflective for transparent	LED, Axial optic	2m Cable	NPN	S5N-PS-2-M03-NN	952001901	
			NPN	S5N-PA-2-T01-NN	952001691	
		M12 Connector	PNP	S5N-PA-2-T01-PP	952001261	
			NPN	S5N-PA-5-T01-NN	952001581	
	LED, Radial optic	2m Cable	PNP	S5N-PA-5-T01-PP	952001271	
			 IO-Link	S5N-PA-5-T01-OZ	952002220	
		M12 Connector	NPN	S5N-PR-2-T01-NN	952001831	
			PNP	S5N-PR-2-T01-PP	952001281	
Luminescence	LED, Axial optic	2m Cable	NPN	S5N-PA-2-U03-NN	952001701	
			PNP	S5N-PA-2-U03-PP	952001301	
		M12 Connector	NPN	S5N-PA-5-U03-NN	952001591	
			PNP	S5N-PA-5-U03-PP	952001311	
		Contrast	2m Cable	NPN	S5N-PA-2-W03-NN	952001711
				PNP	S5N-PA-2-W03-PP	952001321
			M12 Connector	NPN	S5N-PA-5-W03-NN	952001601
				PNP	S5N-PA-5-W03-PP	952001331
		 IO-Link	S5N-PA-5-W03-OZ	952002240		

S5N - STANDARD PLASTIC HOUSING - L/D INPUT MODELS (S5N-PA...PK/NK)

Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-A00-NK	952701072
			PNP	S5N-PA-2-A00-PK	952701002
		M12 Connector	NPN	S5N-PA-5-A00-NK	952701332
		PNP	S5N-PA-5-A00-PK	952701262	
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-A00-NK	952701202
			PNP	S5N-PR-2-A00-PK	952701132
M12 Connector		PNP	S5N-PR-5-A00-PK	952701392	
Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-B01-NK	952701082
			PNP	S5N-PA-2-B01-PK	952701012
		M12 Connector	NPN	S5N-PA-5-B01-NK	952701342
		PNP	S5N-PA-5-B01-PK	952701272	
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-B01-NK	952701212
			PNP	S5N-PR-2-B01-PK	952701142
M12 Connector		PNP	S5N-PR-5-B01-PK	952701402	
Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C01-NK	952701092
			PNP	S5N-PA-2-C01-PK	952701022
		M12 Connector	NPN	S5N-PA-5-C01-NK	952701352
		PNP	S5N-PA-5-C01-PK	952701282	
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-C01-NK	952701222
			PNP	S5N-PR-2-C01-PK	952701152
M12 Connector		PNP	S5N-PR-5-C01-PK	952701412	
Short Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C10-NK	952701102
			PNP	S5N-PA-2-C10-PK	952701032
		M12 Connector	NPN	S5N-PA-5-C10-NK	952701362
		PNP	S5N-PA-5-C10-PK	952701292	
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-C10-NK	952701232
			PNP	S5N-PR-2-C10-PK	952701162
M12 Connector		PNP	S5N-PR-5-C10-PK	952701422	
Through beam receiver	LED, Axial optic	2m Cable	NPN	S5N-PA-2-F00-NK	952701122
			NPN	S5N-PA-5-F00-NK	952701382
	LED, Radial optic	M12 Connector	PNP	S5N-PA-5-F00-PK	952701312
			PNP	S5N-PR-5-F00-PK	952701442
Through beam emitter	LED, Axial optic	2m Cable	-	S5N-PA-2-G00-XG	952001191
		M12 Connector	-	S5N-PA-5-G00-XG	952001201
	LED, Radial optic	2m Cable	-	S5N-PR-2-G00-XG	952001211
		M12 Connector	-	S5N-PR-5-G00-XG	952001221
	LASER, Axial optic	2m Cable	-	S5N-PL-2-G00-XG	952001421
		M12 Connector	-	S5N-PL-5-G00-XG	952001431
	LASER, Radial optic	2m Cable	-	S5N-PH-2-G00-XG	952002061
		M12 Connector	-	S5N-PH-5-G00-XG	952002071

S5N - SHORT PLASTIC HOUSING - L/D INPUT MODELS (S5N-SA...)

Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-SA-2-B00-NK	952301062
			PNP	S5N-SA-2-B00-PK	952301012
Pig Tail M12		PNP	S5N-SA-3-B00-PK	952301122	
2m Cable		NPN	S5N-SA-2-C00-NK	952301072	
		PNP	S5N-SA-2-C00-PK	952301022	
Diffuse proximity		PNP	S5N-SA-3-C00-PK	952301132	
		PNP	S5N-SA-3-C10-PK	952301142	
Short Diffuse proximity		PNP	S5N-SA-3-D50-PK	952301541	
Fixed Focus		PNP	S5N-SA-3-F00-PK	952301152	
Through beam receiver			-	S5N-SA-3-G00-XG	952301212
Through beam emitter		M12 Connector	NPN	S5N-SA-5-M01-NK	952301351
Background suppression			PNP	S5N-SA-5-M01-PK	952301271
			PNP	S5N-SA-5-T01-PK	952301241
Retroreflective for transparent				NPN	S5N-SA-5-T01-NK

S5N - METAL HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-MA...PP/NN/OZ)

Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-MA-2-A00-NN	952022091
		M12 Connector	PNP	S5N-MA-2-A00-PP	952022081
			NPN	S5N-MA-5-A00-NN	952022111
		2m Cable	PNP	S5N-MA-5-A00-PP	952022101
NPN			S5N-MA-2-B01-NN	952021501	
Polarized retroreflective		M12 Connector	PNP	S5N-MA-2-B01-PP	952021001
			NPN	S5N-MA-5-B01-NN	952021661
		LED, Radial optic	PNP	S5N-MA-5-B01-PP	952021201
	IO-Link		S5N-MA-5-B01-OZ	952022160	
	LASER, Axial optic	NPN	S5N-MR-2-B01-NN	952021601	
		PNP	S5N-MR-2-B01-PP	952021141	
		NPN	S5N-MR-5-B01-NN	952021761	
		PNP	S5N-MR-5-B01-PP	952021341	
Long Diffuse proximity	LASER, Radial optic	NPN	S5N-ML-2-B01-NN	952021821	
		PNP	S5N-ML-2-B01-PP	952021401	
	M12 Connector	NPN	S5N-ML-5-B01-NN	952021851	
		PNP	S5N-ML-5-B01-PP	952021441	
	LED, Axial optic	IO-Link	S5N-ML-5-B01-OZ	952022180	
		NPN	S5N-MH-2-B01-NN	952021951	
		PNP	S5N-MH-2-B01-PP	952021941	
		NPN	S5N-MH-5-B01-NN	952021971	
Short Diffuse proximity	LED, Axial optic	PNP	S5N-MH-5-B01-PP	952021961	
		NPN	S5N-MA-2-C01-NN	952021511	
		PNP	S5N-MA-2-C01-PP	952021011	
		NPN	S5N-MA-5-C01-NN	952021671	
	LED, Radial optic	PNP	S5N-MA-5-C01-PP	952021211	
		IO-Link	S5N-MA-5-C01-OZ	952022200	
		NPN	S5N-MR-2-C01-NN	952021611	
		PNP	S5N-MR-2-C01-PP	952021151	
	LASER, Axial optic	NPN	S5N-MR-5-C01-NN	952021771	
		PNP	S5N-MR-5-C01-PP	952021351	
		NPN	S5N-ML-2-C01-NN	952021831	
		PNP	S5N-ML-2-C01-PP	952021411	
	LASER, Radial optic	NPN	S5N-ML-5-C01-NN	952021861	
		PNP	S5N-ML-5-C01-PP	952021451	
		IO-Link	S5N-ML-5-C01-OZ	952022190	
		NPN	S5N-MH-2-C01-NN	952021991	
Medium Diffuse proximity	LED, Axial optic	PNP	S5N-MH-2-C01-PP	952021981	
		NPN	S5N-MH-5-C01-NN	952022011	
		PNP	S5N-MH-5-C01-PP	952022001	
		NPN	S5N-MA-2-C10-NN	952021521	
	LED, Radial optic	PNP	S5N-MA-2-C10-PP	952021021	
		NPN	S5N-MA-5-C10-NN	952021681	
		PNP	S5N-MA-5-C10-PP	952021221	
		NPN	S5N-MR-2-C10-NN	952021621	
Fixed focus	LED, Axial optic	PNP	S5N-MR-2-C10-PP	952021491	
		NPN	S5N-MR-5-C10-NN	952021781	
		PNP	S5N-MR-5-C10-PP	952021481	
		NPN	S5N-MA-2-C21-NN	952022131	
	LED, Radial optic	PNP	S5N-MA-2-C21-PP	952022121	
		NPN	S5N-MA-5-C21-NN	952022151	
		PNP	S5N-MA-5-C21-PP	952022141	
		NPN	S5N-MA-2-D00-NN	952021531	
Fiber optic	LED, Axial optic	PNP	S5N-MA-2-D00-PP	952021031	
		NPN	S5N-MA-5-D00-NN	952021691	
		PNP	S5N-MA-5-D00-PP	952021231	
		NPN	S5N-MR-2-D00-NN	952021631	
	LED, Radial optic	PNP	S5N-MR-2-D00-PP	952021161	
		NPN	S5N-MR-5-D00-NN	952021791	
		PNP	S5N-MR-5-D00-PP	952021361	
		NPN	S5N-MA-2-E01-NN	952021881	
Through beam receiver	LED, Axial optic	PNP	S5N-MA-2-E01-PP	952021041	
		NPN	S5N-MA-5-E01-NN	952021891	
		PNP	S5N-MA-5-E01-PP	952021241	
		NPN	S5N-MA-2-F01-NN	952021541	
	LED, Radial optic	PNP	S5N-MA-2-F01-PP	952021051	
		NPN	S5N-MA-5-F01-NN	952021701	
		PNP	S5N-MA-5-F01-PP	952021251	
		NPN	S5N-MR-2-F01-NN	952021641	
	LASER, Axial optic	PNP	S5N-MR-2-F01-PP	952021171	
		NPN	S5N-MR-5-F01-NN	952021801	
		PNP	S5N-MR-5-F01-PP	952021371	
		NPN	S5N-ML-2-F01-NN	952021841	
	LASER, Radial optic	PNP	S5N-ML-2-F01-PP	952021421	
		NPN	S5N-ML-5-F01-NN	952021871	
		PNP	S5N-ML-5-F01-PP	952021461	
		NPN	S5N-MH-2-F01-NN	952022031	
		PNP	S5N-MH-2-F01-PP	952022021	
		NPN	S5N-MH-5-F01-NN	952022051	
		PNP	S5N-MH-5-F01-PP	952022041	

S5N - METAL HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-MA...PP/NN/OZ)

Through beam emitter	LED, Axial optic	2m Cable	-	S5N-MA-2-G00-XG	952021061	
		M12 Connector	-	S5N-MA-5-G00-XG	952021261	
	LED, Radial optic	2m Cable	-	S5N-MR-2-G00-XG	952021181	
		M12 Connector	-	S5N-MR-5-G00-XG	952021381	
	LASER, Axial optic	2m Cable	-	S5N-ML-2-G00-XG	952021431	
		M12 Connector		S5N-ML-5-G00-XG	952021471	
	LASER, Radial optic	2m Cable	-	S5N-MH-2-G00-XG	952022061	
		M12 Connector	-	S5N-MH-5-G00-XG	952022071	
Background suppression	LED, Axial optic	2m Cable	NPN	S5N-MA-2-M03-NN	952021551	
Background suppression			PNP	S5N-MA-2-M03-PP	952021071	
	LED, Radial optic	M12 Connector	PNP	S5N-MA-5-M03-PP	952021271	
			 IO-Link	S5N-MA-5-M03-OZ	952022170	
			PNP	S5N-MS-5-M03-PP	952021931	
			PNP	S5N-MS-2-M03-PP	952021911	
Retroreflective for transparent	LED, Axial optic	2m Cable	NPN	S5N-MA-2-T01-NN	952021571	
			PNP	S5N-MA-2-T01-PP	952021091	
		M12 Connector	NPN	S5N-MA-5-T01-NN	952021731	
			PNP	S5N-MA-5-T01-PP	952021291	
	LED, Radial optic	2m Cable	NPN	S5N-MR-2-T01-NN	952021651	
			PNP	S5N-MR-2-T01-PP	952021191	
		M12 Connector	NPN	S5N-MR-5-T01-NN	952021811	
			PNP	S5N-MR-5-T01-PP	952021391	
	Luminescence	LED, Axial optic	M12 Connector	PNP	S5N-MA-5-U03-PP	952021301
	Contrast		2m Cable	PNP	S5N-MA-2-W03-PP	952021111
M12 Connector			NPN	S5N-MA-5-W03-NN	952021751	
				PNP	S5N-MA-5-W03-PP	952021311

S5N - METAL HOUSING - L/D INPUT MODELS MODELS (S5N-MA...PK/NK)


Retroreflective	LED, Axial optic	M12 Connector	NPN	S5N-MA-5-A00-NK	952701802	
Polarized retroreflective			PNP	S5N-MA-5-A00-PK	952701532	
			NPN	S5N-MA-5-B01-NK	952701812	
			PNP	S5N-MA-5-B01-PK	952701762	
		Diffuse proximity	2m Cable	NPN	S5N-MA-2-C01-NK	952701622
PNP				S5N-MA-2-C01-PK	952701562	
M12 Connector			NPN	S5N-MA-5-C01-NK	952701822	
			PNP	S5N-MA-5-C01-PK	952701772	
2m Cable			NPN	S5N-MA-2-C10-NK	952701632	
			PNP	S5N-MA-2-C10-PK	952701572	
Through beam receiver			M12 Connector	NPN	S5N-MA-5-C10-NK	952701832
				PNP	S5N-MA-5-C10-PK	952701522
		NPN		S5N-MA-5-F00-NK	952701842	
		PNP		S5N-MA-5-F00-PK	952701782	
Through beam emitter	LED, Axial optic	2m Cable	—	S5N-MA-2-G00-XG	952021061	
		M12 Connector	—	S5N-MA-5-G00-XG	952021261	
	LED, Radial optic	2m Cable	—	S5N-MR-2-G00-XG	952021181	
		M12 Connector	—	S5N-MR-5-G00-XG	952021381	
	LED, Axial optic	2m Cable	—	S5N-ML-2-G00-XG	952021431	
		M12 Connector	—	S5N-ML-5-G00-XG	952021471	
	LED, Radial optic	2m Cable	—	S5N-MH-2-G00-XG	952022061	
		M12 Connector	—	S5N-MH-5-G00-XG	952022071	

S5N - INOX HOUSING - L/D INPUT MODELS MODELS (S5N-NA...)


Polarized retroreflective	LED, Axial optic	M12 Connector	NPN	S5N-NA-5-B01-NK	952301461
Diffuse proximity Inox			PNP	S5N-NA-5-B01-PK	952301381
			NPN	S5N-NA-5-C11-NK	952301481
Through beam receiver Inox			PNP	S5N-NA-5-C11-PK	952301401
			NPN	S5N-NA-5-F01-NK	952301511
Through beam emitter inox			PNP	S5N-NA-5-F01-PK	952301431
			-	S5N-NA-5-G01-XG	952301441
Background suppression inox			NPN	S5N-NA-5-M01-NK	952301501
			PNP	S5N-NA-5-M01-PK	952301421
Retroreflective for transparent inox			NPN	S5N-NA-5-T01-NK	952301471
			PNP	S5N-NA-5-T01-PK	952301391

ACCESSORIES


ST-5010




ST-5011




ST-5012




ST-5017




SWING-18





SP-40




JOINT 18



MICRO 18



M18 FLARED PLASTIC NUT



mm

MODEL	DESCRIPTION	ORDER No.
ST-5010	M18/14 mounting bracket	95ACC5230
ST-5011	M18 mounting bracket short	95ACC5240
ST-5012	M18 mounting bracket long	95ACC5250
ST-5017	M18 mounting bracket	95ACC5270
S50 EASY -IN	M18/14 EASY in™ adjustable mounting support	95ACC 5300
JOINT -18	M18 jointed support	95ACC 5220
MICRO -18	support with micrometric regulation for tubular M18 sensors	95ACC 1380
SP-40	mounting bracket tubular	95ACC1370
SWING-18	adjustable support for M18 tubular sensors	895000006
PLASTIC NUT	flared mounting nut	95ACC2630
M18 FLARED NUT	S5N mounting nut M18 flared nut (1 pc)	95ACC2630
M18 METAL NUT	S5N mounting nut M18 nut (1 pc)	G602000017
M18 PLASTIC NUT KIT	S5N mounting nut M18 nuts kit (100 pcs)	G602000008
MEK -PROOF	front protection (only for metal models)	G5000001

IO-LINK CONNECTIVITY

MODEL	DESCRIPTION	ORDER No.
CBX-8IOL-EIP	CBX-8IOL-EIP 8P IOL M12 EIP MASTER	95ACC8180
CBX-8IOL-PNIO	CBX-8IOL-PNIO 8P IOL M12 PROFINET MASTER	95ACC8190

CABLES

TYPE	DESCRIPTION	LENGTH	MODEL	ORDER No.
Axial M12 Connector	4-pole, grey, P.V.C.	3 m	CS-A1-02-G-03	95A251380
		5 m	CS-A1-02-G-05	95A251270
		7 m	CS-A1-02-G-07	95A251280
		10 m	CS-A1-02-G-10	95A251390
	4-pole, P.U.R.	2 m	CS-A1-02-R-02	95A251540
		5 m	CS-A1-02-R-05	95A251560
Radial M12 Connector	4-pole, grey, P.V.C.	3 m	CS-A2-02-G-03	95A251360
		5 m	CS-A2-02-G-05	95A251240
		7 m	CS-A2-02-G-07	95A251245
		10 m	CS-A2-02-G-10	95A251260
	4-pole, P.U.R.	2 m	CS-A2-02-R-02	95A251550
		5 m	CS-A2-02-R-05	95A251570
Radial M12 Connector with LED (for PNP N.O. sensors)	4-pole, grey, P.V.C.	3 m	CS-A2-12-G-03	95A251400
		5 m	CS-A2-12-G-05	95A251350
		10 m	CS-A2-12-G-10	95A251370
Axial M12 Connector	4-pole, shielded, black, P.V.C.	3 m	CV-A1-22-B-03	95ACC1480
		5 m	CV-A1-22-B-05	95ACC1490
		10 m	CV-A1-22-B-10	95ACC1500
		15 m	CV-A1-22-B-15	95ACC2070
		25 m	CV-A1-22-B-25	95ACC2090
Radial M12 Connector	4-pole, shielded, black, P.V.C.	3 m	CV-A2-22-B-03	95ACC1540
		5 m	CV-A2-22-B-05	95ACC1550
		10 m	CV-A2-22-B-10	95ACC1560
Axial M12 Connector	4-pole, U.L., black, P.V.C.	3 m	CS-A1-02-U-03	95ASE1120
		5 m	CS-A1-02-U-05	95ASE1130
		10 m	CS-A1-02-U-10	95ASE1140
		15 m	CS-A1-02-U-15	95ASE1150
		25 m	CS-A1-02-U-25	95ASE1160
	4-pole, black	Connector- not cabled	CS-A1-02-B-NC	G5085002
Radial M12 Connector	4-pole, black	Connector- not cabled	CS-A2-02-B-NC	G5085003
Axial M12 Connector	5-pole, L coded power cable	3 m	CS-M1-02-B-03	95ACC0007
Axial M12 F/M12 M Connector	4-pole, double headed	3 m	CS-I1-02-B-03	95ACC0009

DS-S5N-SERIES-EN Rev E 20211208