HKF1-11



Products Low Voltage Products and Systems Control Products Manual Motor Starters Manual Motor Starters Accessories

Parts & Services Drives Medium voltage AC drives Industrial drives ACS2000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS1000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS5000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS6000

General Information

Extended Product Type: HKF1-11

Product ID: 1SAM201901R1001 **EAN:** 4013614320354

Catalog Description: HKF1-11 Auxiliary Contact

Long Description: HKF1-11 Aux.-contact for frontmounting

Additional Information

ABS Certificate:	1SAA963001-0101			
Accessory Type:	Auxiliary Contact			
Ambient Air Temperature:	Operation -20 +55 °C Storage -50 +80 °C			
BV Certificate:	1SAA963002-0201			
CB Certificate:	1SAA963003-2001			
CCC Certificate:	1SAA918002-3802			
Connecting Capacity Auxiliary Circuit UL/CSA:	Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG			
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 1.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 1.5 mm ² Flexible 1/2x 0.75 1.5 mm ² Rigid 1/2x 1.0 2.5 mm ²			
Contact Rating UL/CSA:	B300 R300			
Core Credit:	0.00			
Country of Origin:	Bulgaria (BG)			
Customs Tariff Number:	85365080			
DNV Certificate:	1SAA963001-0303			
Data Sheet, Technical Information:	1SBC100192C02			
Declaration of Conformity - CE:	1SAD938500-0198 1SAD938500-0197 1SAD938510-0125 1SAD938502-0190 1SAD938501-0191 1SAD938502-0188			
E-nummer:	3112001			
EAC Certificate:	1SAA963000-2701			
EAN:	4013614320354			
ETIM 4:	EC002498 - Accessories for low-voltage switch technology			
ETIM 5:	EC000041 - Auxiliary contact block			
ETIM 6:	EC000041 - Auxiliary contact block			
GL Certificate:	1SAA963001-0401 1SAA963000-0402			
GOST Certificate:	1SAA937000-2703			
IIT Publishing Status:	Level 0 - Information enabled			

Industrial IT Certification Level:	0		
Instructions and Manuals:	2CDC131011M6802		
	2CDC131034M6801		
Lucia Businita	2CDC131022M6802		
Invoice Description:	HKF1-11 Auxcontact for frontmounting		
LR Certificate:	1SAA963001-0501 1SAA963001-0502		
	1SAA963000-0505		
Maximum Operating Voltage UL/CSA:	Main Circuit 250 V AC		
Minimum Order Quantity:	1 piece		
Mounting Position:	Position 1 to 6		
Number of Auxiliary Contacts NC:	1		
Number of Auxiliary Contacts NO:	1		
Object Classification Code:	Q		
Package Level 1 EAN:	4013614481413		
Package Level 1 Gross Weight:	0.195 kg		
Package Level 1 Height:	50 mm		
Package Level 1 Length:	36 mm		
Package Level 1 Units:	10 piece		
Package Level 1 Width:	148 mm		
Package Level 2 EAN:	4013614522727		
Package Level 2 Height:	210 mm		
Package Level 2 Length:	395 mm		
Package Level 2 Width:	280 mm		
Part Type:	New		
Product Main Type:	HKF1		
Product Name:	Auxiliary Contact		
Product Net Depth:	26.5 mm		
Product Net Height:	12.5 mm		
Product Net Weight:	0.015 kg		
Product Net Width:	45 mm		
RINA Certificate:	1SAA963000-0802		
Rated Impulse Withstand Voltage (U_{imp}):	Auxiliary Circuit 6 kV		
Rated Insulation Voltage (U _i):	250 V		
Rated Operational Current AC-15 (I _e):	(240 V) 4 A		
	(24 V) 6 A (380 / 400 V) 3 A		
	(380 / 400 V) 3 A (690 V) 1 A		
Rated Operational Current DC-13 (I _e):	(125 V) 0.55 A		
• •	(24 V) 2 A		
	(250 V) 0.27 A		
Rated Operational Voltage:	(250 V) 0.27 A (440 V) 0 A		
Rated Operational Voltage: Recommended Screw Driver:	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A		
	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V		
	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V		
Recommended Screw Driver:	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2		
Recommended Screw Driver: RoHS Date:	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2		
Recommended Screw Driver: RoHS Date: RoHS Information:	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2 0276 1SAA963001-4407		
Recommended Screw Driver: RoHS Date: RoHS Information: RoHS Status:	(250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2 0276 1SAA963001-4407 Following EU Directive 2002/95/EC August 18, 2005 and amendment		

Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS116 MS132 MO132
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Auxiliary Circuit 0.8 1.2 N·m
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in·lb
UL Certificate:	UL_E137861
UNSPSC:	39121500
Wire Stripping Length:	Auxiliary Circuit 8 mm
cUL Certificate:	cUL_E137861
eClass:	7.0 27371302

Where Used (as a spare part for "Products")

4 Products Filter

Identifier	Description	Qty	Unit Of Measure
ACS 1000	No Description Available	1	piece
ACS 2000	No Description Available	1	piece
ACS 5000 Water Cooled	No Description Available	1	piece
ACS 6000	No Description Available	1	piece

Product specific part data

4 Products Filter

Product	Category	Drive Part Category
ACS 2000	ACS2000	Switches, Relays, Contactors
ACS 1000	ACS1000	Switches, Relays, Contactors
ACS 5000 Water Cooled	ACS5000	Switches, Relays, Contactors
ACS 6000	ACS6000	Switches, Relays, Contactors

