



THB.387.N4A.XD

MADE IN ITALY



TH387 - mini-Plug&Socket connector (xDRY® anti-condensation) IP66/IP68

NEW XDRY®



IP66 IP68 xDRY



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP66/IP68 Plug&Socket circular connectors
Product name (Series)	TH387 - mini-Plug&Socket connector (xDRY® anti-condensation) IP66/IP68
Product configuration	Panel-mounted plug connector with fixing nut <small>* Fixing nut included in the kit.</small>
Thread	M20
Panel thickness min. - max.	1.0 mm - 9.0 mm
Colour	black/Verde (Componenti plastici) - Verde (Componenti gomma)
Outer dimension	Φ 23 mm x (61 ÷ 76 mm) (when plug-socket matched)

i xDRY®: Connectors protected from water and dust (IP68) with anti-condensation barrier. The xDRY® system prevents the damp inside the cable from entering the connection and proceeding towards the device installed.

ELECTRICAL CHARACTERISTICS

Number of poles	4
Contact marking	1 - 2 - 3 - 4(E)
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 17.5A
Operating voltage	max. 450V AC
Impulse withstand voltage	4KV

i Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP66/IP68 (30m,3h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

i Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm ² - 4.0 mm ²
Wire cross-section min. - max. (Solid cable)	0.5 mm ² - 4.0 mm ²

MATERIAL CHARACTERISTICS

Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	TPE-S
Grommets	TPE-S
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)



Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free
T marking	T 125°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

i Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009
-----------------	---------------

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 products/box
Unit weight	15,48 gram/product
Box dimension	300 x 200 x 160

INSTALLATION INSTRUCTIONS

- Guidelines Installation PDF • 753 KB
- 606002031 TH387 parete v02 Lungo PDF • 474 KB
- IST TH387 parete v02 PDF • 691 KB
- Techno AssemblyTH387 PDF • 1 MB