



THH.623.L3A

MADE IN ITALY



TH623 - Current distributor 4 ways type "H"

IP68



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEBOX® Current Distributors - IP68 Junction boxes pre-wired with plug&socket connectors
Product name (Series)	TH623 - Current distributor 4 vie tipo "H"
Product configuration	Junction box with plug and socket connectors <small>* Connettori presa-spina inclusi nell'imballo</small>
Type of Fixation	With fixing screws on flat surface
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	200 mm x 65 mm x 28 mm (when plug-socket matched)

ELECTRICAL CHARACTERISTICS

Number of poles	3
Contact marking	L - N - E
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 17.5A
Operating voltage	max. 400V AC
Impulse withstand voltage	4KV

Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (5m,3h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS


Wire cross-section min. - max. (Stranded cable)	0.5 mm ² - 4.0 mm ²
Wire cross-section min. - max. (Solid cable)	0.5 mm ² - 4.0 mm ²
Cable diameter min. - max.	7.0 mm - 12.0 mm (main cable) / 7.0 mm - 12.0 mm (branch cable) <small>* For cables with diameter For smaller cables please take the proper accessory.</small>

MATERIAL CHARACTERISTICS

Body	PA66 UL94 V2 GWT 850°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2



Material properties	Halogen Free
T marking	T 85°C
Operating temperature range	-40°C/+125°C
Proof Tracking Index (PTI)	PTI 175

 Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009
-----------------	---------------

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	50 products/box
Unit weight	211,3 gram/product
Box dimension	400 x 230 x 400

INSTALLATION INSTRUCTIONS

- [IST TH622-623 v01](#) PDF • 349 KB
- [Guidelines Installation](#) PDF • 753 KB

CERTIFICATIONS AND TEST REPORTS

- [TH623 Nemko EN60998](#) PDF • 311 KB
- [CE-TH623](#) DOC • 196 KB

MARKETING COLLATERALS

- [Pannello 6](#) PDF • 388 KB
- [PUBBdistributori](#) PDF • 2 MB