



THB.384.A1A

MADE IN ITALY



TH384 - mini-Plug&Socket connector IP66/IP68

IP66 **IP68**



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP68 Plug&Socket circular connectors
Product name (Series)	TH384 - mini-Plug&Socket connector IP66/IP68
Product configuration	Plug connector (cable-to-cable)
Type of Fixation	With quick-fix mounting clip * Supporto da ordinare separatamente (code 6000302CC).
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 27 mm x 95 mm (when plug-socket matched)

ELECTRICAL CHARACTERISTICS

Number of poles	3
Contact marking	L - N - E
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 17.5A (EN61984) - max. 20A (UL2238/C22.2 No. 182.3)
Operating voltage	max. 400V AC
Impulse withstand voltage	4KV

Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP66/IP68 (50m,24h)
Protection against impact (IK)	IK08
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm ² - 4.0 mm ² (12 AWG)
Wire cross-section min. - max. (Solid cable)	0.5 mm ² - 4.0 mm ² (12 AWG)
Cable diameter min. - max.	7.0 mm - 12.0 mm * For cables with diameter For smaller cables please take the proper accessory.

MATERIAL CHARACTERISTICS

Body	PA66 UL94 V2 GWT 850°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	TPE
Grommets	TPE
Contacts	CuZn (silver plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II



Pollution degree	2
Material properties	Halogen Free - Silicone Free
T marking	T 85°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

i Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009 - UL2238/C22.2 No. 182.3
-----------------	--

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 products/box
Unit weight	16,9 gram/product
Box dimension	400 x 210 x 170

INSTALLATION INSTRUCTIONS

- IST TH380-382-384-385 v01 PDF • 582 KB
- Guidelines Installation PDF • 753 KB

CERTIFICATIONS AND TEST REPORTS

- • 273 KB
- CE-TH384 DOC • 205 KB
- TH384 CA0204851 PDF • 651 KB

MARKETING COLLATERALS

- pannello techno 06 vert 80x120 LOW
PDF • 635 KB

DRAWINGS

- THB384A1ASTEP
• 888 KB • CONFIDENTIAL DOCUMENT